EGHOLM

Rotary/mulch mower 1200

- Park Ranger 2150

Standard equipment:

Tilting for cleaning	The mower can tilt up and rest on two support wheels making cleaning easy.
Piano wheels	Piano wheels which move the cutter in line with the manoeuvring are equipped with heavy slide bearings in their wheel forks for durability.

Extra equipment (options):

To avoid choking of the radiator grill while mowing dry grass in dusty surroundings, the large radiator cover Large radiator cover can be fitted.

The rotary mower can be changed into a mulch mower with a cover placed inside the same mowing deck. Mulch mower kit Mulching creates fine trimmings, which supply the soil with natural nutrients and reduces the need of fertilisers.





Technical specifications

Dimensions		
Length	mm	2780
Width	mm	1290
Height with / without cabin	mm	1935 / 1210
Storage dimensions		
Length	mm	980
Width	mm	1290
Height	mm	480
Weight		
Weight (rotary mower)	kg	103
Performance		
Ground clearance below mower	mm	110
No. of mower blades	pcs.	2
Cutting speed (tip speed)	m/sec.	77
Cutting width	mm	1210
Adjustable cutting height	mm	30-70
Theoretical mowing area - rotary	m²/h	15600
Theoretical mowing area - mulch	m²/h	12000
Max. recommended operating speed		
Rotary mower *	km/h	10
Mulch mower (shorter grass) *	km/h	10
* Depends on grass and height		
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	104
CE certified according to EU directive		





