


Snow sweeper

- Park Ranger 2150



1220 mm



3020 mm

1935 mm

Standard equipment:

- Trapeze mounting** The trapeze-mounting ensures the snow sweeper remains clear of the wheels of the utility machine at all times, whatever the angle. The snow sweeper automatically turns with the utility machine - always sweeping in front of the wheels of the utility machine.
- Reverse rotation function** Reversing the brush rotation ensures that the operator can sweep material when reversing out of an alley or parking spot, which ensures an excellent result.
- Adjustable speed** The rotation speed can easily be adjusted from the cabin to match the need for sweeping.
- Support stand** A support stand with a wheel is built into the snow sweeper for easy storage.

Extra equipment (options):

- Extended brush guard** Attaching a brush guard extends the snow sweeper cover, which minimises the snow whirling up on the front wind-screen. Furthermore, the guard makes it easier to control the direction of swept sand and gravel during summer operation. This can be retrofitted on existing snow sweepers as well.
- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	3020
Width	mm	1220
Height with cabin	mm	1935

Storage dimensions

Length	mm	900
Width	mm	1220
Height	mm	650

Weight

Weight (snow sweeper)	kg	101
-----------------------	----	-----

Performance

Clearing width - straight	mm	1220
Clearing width - angled 25°	mm	1140
Ground clearance below brush	mm	420
Brush diameter Ø	mm	550
Operating speed	km/h	1-10
Theoretical sweeping capacity	m ² /h	12200
Handling snow depth up to	mm	150
Brush speed	rpm	255
Turning angle		25°

CE certified according to EU directive

