

Grass collector

- City Ranger 2260





1939 mm 2060 mm

1285 mm

Technical specifications

Standard equipment:

Stand / frame

The supplied frame allows for simple and quick attaching and removal of the hopper. The stand is also used for storing the hopper.

Hydraulic emptying function

The hopper can be emptied without leaving the seat. The hydraulic tip function is controlled from the joystick and the cover on the hopper opens automatically when tilted.

The tipping height can be adjusted from 575 to 1860 mm allowing for tipping directly into containers within this height range.

Extra equipment (options):

Leaf collection hose

It is also possible to remove leaves with the grass collector. When a leaf collection hose is fitted on the hopper, you can remove leaves in places where the mower cannot work - up to 6 m. The lightweight leaf collection hose is discretely fitted on the top of the hopper, when not in use.

Grass panel (10 mm)

The hopper is supplied with a 5 mm grass filter as standard, to minimise airborne deposits when working with dry grass. A 10 mm grass filter increases airflow and suction power, and is an advantage when working with damp and heavy grass.

Plastic panel

Used for very damp and sticky grass. The plastic panel is inserted into the hopper to prevent the grass filter from becoming blocked.

Mulch mover & rotary mower kits

You can quickly convert the grass collector to a non-collecting mulch mower or standard rotary mower with the help of special kits available.

Dimensions

Differsions		
Length (with mower 1200)	mm	3230
Width (with mower 1200)	mm	1285
Height with cabin / roll bar (ROPS)	mm	1939 / 2060
Height with leaf collection hose	mm	2150
Storage dimensions		
Length	mm	1700
Width	mm	940
Height with / without collection hose	mm	2150 / 1950
W-:-ka-		
Weights	Les	1040 / 1010
Weight with cabin / roll bar (ROPS) 1)	kg	1242 / 1212
Payload with cabin / roll bar (ROPS)	kg	368 / 398
Weight (grass collector)	kg	202
Weight - frame	kg	31
Hopper (grass collector)		
Hopper volume	I	750
Hopper load, max.	kg	300
Tipping height, minmax.	mm	575-1860
Performance		
Air flow	m³/h	2400
Air speed	km/h	120
Operating speed	km/h	1-10
Noise emissions		
Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	105
CE certified according to EU directive		
1) Includes: grass collector, mower 1200, 75 kg operator and 90% fu	L el capacity	

¹⁾ Includes: grass collector, mower 1200, 75 kg operator and 90% fuel capacity.





