

Snow blower

- City Ranger 3070



Standard equipment:

- Hydraulic adjustment of the chute** The vertical and horizontal direction of the chute is hydraulically adjusted via the joystick from inside the cabin.
- Safety feature** In case of clogging, the in-take of the machine is equipped with spring bolts to protect it from over-stress.
- Adjustable weight distribution** For optimum functionality as well as minimum wear of the attachment.
- Skid** The 2 skids are height adjustable to ensure that the blade adjusts to surface variations.
- Blade** The snow blower has a replaceable blade.

Extra equipment (options):

- Tyres 235/60 R 16 (M+S)** The wide tyres are also suitable for winter service. They also have an M+S identifier (snowflake), but generate less ground pressure.
- Tyres 195/70 R 15 (M+S)** When using snow chains, we recommend 15" tyres. Like the 16" wheels, these tyres also have an M+S code and are suitable for winter service use.
- Anti-corrosion treatment** The anti-corrosion treatment will extend the life of the attachment.

Technical specifications

Dimensions

Length	mm	4700
Width	mm	1330
Height / with beacon	mm	2300 / 2300

Storage dimensions

Length	mm	1120
Width	mm	1330
Height	mm	1800

Weight

Weight (snow blower)	kg	285
----------------------	----	-----

Performance

Clearing width	mm	1300
Feed intake height	mm	700
Ground clearance below snow blower	mm	390
Auger diameter	mm	400
Blower diameter	mm	400
Auger revolutions per minute	rpm	0-1100
Operating speed	km/h	1-7

Noise emissions

Sound power level LwA (2000/14/EC and DIN EN ISO 3744)	dB(A)	106
--	-------	-----

CE certified according to EU directive

